

# CK 615

## Curing Agent D

Ready-for-use curing agent for concrete

### CHARACTERISTICS

- ▶ economical spray application
- ▶ for use on green concrete and screed surfaces
- ▶ prevents too rapid drying
- ▶ solvent- and wax-free

### SCOPE OF USE

CK 615 Curing Agent D is a liquid, dispersion-based concrete curing compound. It protects the green concrete or screed against dehydration, i.e. the removal of water required for hardening. It replaces the time- and labour-consuming curing of demoulded areas. CK 615 Curing Agent D successfully prevents too rapid drying (dehydration), thus preventing the screed from curling and the concrete members from cracking.

### APPLICATION

CK 615 Curing Agent D comes ready for use and must only be applied in its undiluted form. Apply a thin and uniform film (required amount: see Technical Data) on the concrete/screed to be protected. We recommend using our CK 319 Special Spray Device, supplied with a round jet nozzle, to ensure a uniform and economical application of the agent.

Thoroughly stir CK 615 Curing Agent D before use. Then apply a continuous film onto the slightly damp or demoulded substrate. The curing agent film does not affect the adhesion of subsequently used commercial paints or plastic-modified tile adhesives.

In the case of extreme weather conditions or special concreting methods, additional curing steps may be necessary.



### PLEASE NOTE

CK 615 Curing Agent D must not be used as an additive and admixed directly to the fresh concrete! Observe the warnings-, safety- and waste disposal advice given in the safety data sheet.

**Should you need support or advice, please consult our advisory service for architects and craftsmen on the hotline numbers**

**Phone: +49 211 797 0**

**Fax: +49 211 798 2148**


## TECHNICAL DATA

Density:	approx. 1.0 kg/dm <sup>3</sup>
Material base:	copolymer
Physical state / colour:	liquid / milky white
Cleaning agent:	water
Rainproof:	after drying
Application temperature:	+5 °C to +30 °C
Required amount:	approx. 200 g/m <sup>2</sup>
Shelf life:	Approx. 12 months in a cool but frost-free place. Use up opened containers as quickly as possible.

Apart from the information given here it is also important to observe the relevant guidelines and regulations of various organisations and trade associations as well as the respective standards of the German Standards Institute (DIN). The aforementioned characteristics are based on practical experience and applied testing. Warranted properties and possible uses which go beyond those warranted in this information sheet require our written confirmation. All data given was obtained at an ambient and material temperature of +23 °C and 50 % relative air humidity unless specified otherwise. Please note that under other climatic conditions hardening can be accelerated or delayed.

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience. As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of wilful misconduct or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.

Henkel AG & Co. KGaA – Bautechnik  
Henkelstraße 67 · D-40589 Düsseldorf  
Telefon +49 211 797 0 • Telefax +49 211 798 2148  
Internet: [www.ceresit.com](http://www.ceresit.com) · E-Mail: [ceresit.bautechnik@henkel.com](mailto:ceresit.bautechnik@henkel.com)



Build on professional solutions.